

D&B 10-D EXPLORATION/GEOTECH

Specifically designed to bridge the gap between geotechnical and exploration drilling.

With a top head drive, 3.8m stroke and a collapsible top half of the mast, it's a compact unit that won't look out of place on a mineral or geotechnical job.

STANDARD SPECIFICATIONS

MAIN WINCH	5,000kg
RETRACT FORCE	12,000kg
RETRACT SPEED	30m/min
PULL DOWN FORCE	6,000kg
PULL DOWN SPEED	35m/min
HEAD STROKE	3800mm
KW	78
ENGINE	D4DA
ROTATION TORQUE	4,120Nm @ 0-100 RPM

*DEPTH CAPABILITY

PWL (114.3mm)	Up to 100m
HWL (88.9mm)	Up to 200m
NWL (69.9mm)	Up to 500m
BWL (55.6mm)	Up to 750m

BASIC RIG DIMENSIONS

OA LENGTH	5.5M
OA WIDTH	2M
OA TRANSPORT HEIGHT	2.3M
HEIGHT (MAST RAISED VERTICALLY)	5.8M
DRY WEIGHT (DEPENDENT)	5.8T

TRUCK OR
TRACK
MOUNTED



STANDARD EQUIPMENT

WIRELESS REMOTE CONTROL FOR TRAVEL
350MM 150KG EXTENDABLE JIB BOOM
WIRELINE WINCH
5T MAIN WINCH
SELF LOADING JACK LEGS
MANUAL BREAKOUT TABLE CLAMP - 10" DIA
FOOTCLAMP P,H,N JAWS
HOSE COVERING
RISK ASSESMENT

OPTIONAL EXTRAS

450/500 ON BOARD COMPRESSOR
AMERICAN AW11 PUMP
300LPM DUPLEX MUD PUMP
ROD LOADING SYSTEM
WATER INJECTION PUMP
AMERICAN TRIPLEX PISTON PUMP
RC KIT AVAILABLE
ONBOARD WELDER

*Under normal drilling conditions

**DISCOVER OUR
CAPABILITIES**

Call: +61 3 5445 6900
Email: sales@mccullochs.com.au
Visit: mccullochsdrilling.com



McCULLOCHS
DRILLING & BORING

