D&B12-D MULTIPURPOSE

Specifically designed to bridge the gap between geotechnical and exploration drilling.

A medium depth multi purpose rig the 12-D is able to carry out a wide scope of drilling processes, from open hole hammer to wireline coring. This model is available with a long list of accessories and can also be track or truck mounted to offer a solution no matter what terrain vou're drilling in.

STANDARD SPECIFICATIONS

MAIN WINCH	5,000kg	TRUC
RETRACT FORCE	10,000kg	TRA
RETRACT SPEED	30m/min	ΜΟυι
PULL DOWN FORCE	6,000kg	
PULL DOWN SPEED	35m/min	
HEAD STROKE	6.5M	
KW	93	
ENGINE	HYUNDAI D4DA	
ROTATION TORQUE	4,120Nm @ 0-120 RPM	

***DEPTH CAPABILITY**

PWL (114.3mm)	Up to 100m
HWL (88.9mm)	Up to 200m
NWL (69.9mm)	Up to 500m
BWL (55.6mm)	Up to 750m

BASIC RIG DIMENSIONS

OA LENGTH	7.9M
OA WIDTH	2M
OA TRANSPORT HEIGHT	2.5M
HEIGHT (MAST RAISED VERTICALLY)	8.1M
DRY WEIGHT (DEPENDING)	7Т



K OR СК NTED

STANDARD EQUIPMENT

WIRELESS REMOTE **CONTROL FORTRAMMING** WIRELINE WINCH SELF LOADING JACK LEGS MANUAL BREAKOUT FOOT CLAMPS, P,H,N **JAWS HOSE COVERING RISK ASSESMENT** W1122 WATER PUMP

OPTIONAL EXTRAS

450/500 ON BOARD COMPRESSOR **300LPM MUD PUMP ROD LOADING SYSTEM** WATER INJECTION PUMP **RC KIT AVAILABLE ONBOARD WELDER**

*Under normal drilling conditions



Call: +61 3 5445 6900 Email: sales@mccullochs.com.au Visit: mccullochsdrilling.com







