

# D&B 16-MULTI

A robust design allows the rig to cover a wide variety of drilling styles and depths whilst still allowing for practical mobilisation.

Designed to bridge the gap between medium depth and deep hole exploration, the 16-Multi is able to be track or truck mounted and is equipped for diamond coring, RC, and everything in between.

With 16t pullback, 6m rod capacity and maximum casing diameter of 10" this model is well equipped to cover all of your drilling needs.

## STANDARD SPECIFICATIONS

MAIN WINCH	10,000kg
RETRACT FORCE	16,000kg
RETRACT SPEED	30m/min
PULL DOWN FORCE	8,000kg
PULL DOWN SPEED	35m/min
HEAD STROKE	7m
HP	180
ENGINE	HYAUNDAI D 6BT
ROTATION SPEED	1100 rpm

## \*DEPTH CAPABILITY

PWL (114.3mm)	Up to 300m
HWL (88.9mm)	Up to 500m
NWL (69.9mm)	Up to 1,000m
BWL (55.6mm)	Up to 1,500m

## BASIC RIG DIMENSIONS

OA LENGTH	11.4M
OA WIDTH	2.2M
OA TRANSPORT HEIGHT	2.9M
HEIGHT (MAST RAISED VERTICALLY)	12M
DRY WEIGHT (DEPENDING)	10T

TRUCK OR  
TRACK  
MOUNTED



**McCULLOCHS**  
DRILLING & BORING

## STANDARD EQUIPMENT

WATER INJECTION  
180HP 6CYL HYUNDAI  
1.9M 250KG EXTENDABLE  
JIB CRANE  
7M HEAD TRAVEL  
WIRELINE WINCH  
SELF-LOADING JACKS  
WIRELESS REMOTE FOR  
TRAVEL  
RISK ASSESMENT  
MANUAL BREAKOUT  
TABLE BREAKOUT

## OPTIONAL EXTRAS

300LPM MUD PUMP  
AMERICAN TRIPLEX  
PISTON PUMP  
350/500 COMPRESSOR  
RC KIT WITH CYCLONE  
ROD LOADER  
TRUCK MOUNTING

\*Under normal drilling conditions

**DISCOVER OUR  
CAPABILITIES**

Call: +61 3 5445 6900  
Email: [sales@mccullochs.com.au](mailto:sales@mccullochs.com.au)  
Visit: [mccullochsdrilling.com](http://mccullochsdrilling.com)



**McCULLOCHS**  
DRILLING & BORING

